


Loudoun County, Virginia

An aerial photograph of a long, multi-span bridge crossing a wide river. The bridge has a white truss structure and a paved roadway. The river is greenish-brown, and the surrounding landscape is covered in green trees and vegetation. The text "2014 Water Resources Monitoring Data Summary" is overlaid in large, bold, white letters with a black outline.

2014 Water Resources Monitoring Data Summary

December 2015

Potomac River near Point of Rocks, MD – 2015 Pictometry

2014 Water Resources Monitoring Data Summary



**Loudoun County, Virginia
Department of Building and Development
Engineering Division
Water Resources Team**

December 2015

ABBREVIATIONS AND ACRONYMS

<i>cfs:</i>	<i>cubic feet per second</i>
<i>DEQ:</i>	<i>Virginia Department of Environmental Quality</i>
<i>EPA:</i>	<i>U.S. Environmental Protection Agency</i>
<i>MCL:</i>	<i>maximum contaminant level</i>
<i>mg/L:</i>	<i>milligrams per Liter</i>
<i>NWS-COOP:</i>	<i>National Weather Service Cooperative monitoring station</i>
<i>OWTS:</i>	<i>On-site Wastewater Treatment System</i>
<i>TDS:</i>	<i>Total Dissolved Solids</i>
<i>uS/cm:</i>	<i>microSiemens per centimeter</i>
<i>USGS:</i>	<i>U.S. Geological Survey</i>
<i>WRMP:</i>	<i>Water Resources Monitoring Program (Loudoun County)</i>
<i>NWS:</i>	<i>National Weather Service (Division of National Oceanographic and Atmospheric Administration)</i>

DATA LIMITATIONS

While efforts have been made to insure the accuracy of the data presented in this report, Loudoun County does not assume any liability arising from the use of these data. Reliance on these data is at the risk of the user. The U.S. Geological Survey (USGS) and the National Climatic Data Center (who distribute National Weather Service data) have data quality assurance procedures in which data are considered “provisional” until they are checked and corrected as needed. Data used in this report that are provisional are:

- USGS rainfall site Limestone/Leesburg, 11/05/2013 - 12/31/2014
- USGS rainfall site Catoctin/Lovettsville, 11/05/2013 - 12/31/2014
- USGS stream gaging station, typically from 11/06/2013 through 12/31/2014

HYPERLINKS

The underlined text in this document indicates hyperlinks to additional data and online resources that may be accessed when this document is opened in a program designed to view portable document format (pdf) files. The report can be found at www.loudoun.gov/watermonitoring and follow the link to Data Analysis & Reporting.

ACKNOWLEDGMENTS

This document was prepared by County staff members David Ward, Dennis Cumbie, and Glen Rubis of the Water Resources Team in the Engineering Division of the Department of Building and Development.

Loudoun County, VA
2014 Water Resources Monitoring Data Summary

Table of Contents

Introduction and Setting.....	1
General Characteristics of Loudoun County	1
Physiography and Geology.....	2
Watersheds	2
Water Quantity	3
Precipitation.....	3
Snowfall.....	3
Streamflow.....	5
Groundwater Levels and Wells	6
Water Quality	8
Surface Water Chemistry	8
Surface Water Microbiology.....	9
Benthic Macroinvertebrates.....	10
Stream Health Trend	11
Stream Impairments.....	11
Groundwater Quality.....	13
Future Water Resources Outlook	14

INTRODUCTION AND SETTING

This document summarizes data collected during various water resources monitoring activities in and adjacent to Loudoun County, Virginia, by government, private and volunteer organizations during calendar year 2014. Specifically, data characterizing precipitation, streamflow, groundwater levels, and surface water and groundwater quality are presented. Loudoun County Department of Building and Development either collects these data or compiles them from other sources as part of the County's Water Resources Monitoring Program (WRMP). The data are presented and discussed in two sections: water quantity – measurements of precipitation, streamflows, and groundwater levels; and water quality – the chemical and biological characteristics of stream water and groundwater.

The WRMP was initiated in 2001 to help assess the conditions of water resources in Loudoun County, which has been one of the fastest growing counties in the nation during the past decade. The estimated population of Loudoun in 2014 is over 363,000 and is forecast to reach 471,000 by 2030; an increase of 30 percent.

General Characteristics of Loudoun County

Loudoun County is located in Northern Virginia approximately 30 miles west of Washington, D.C. The county covers an area of 521 square miles and is bordered on the north by the Potomac River and the west by the Blue Ridge Mountains (Figure 1).

Urban and suburban development is concentrated mostly in the eastern part of the county, generally from the Town of Leesburg to Washington Dulles International Airport and the border with Fairfax County. The western portion of the county is more rural, with crop farms, pastures, vineyards, several small towns, and numerous large-lot residential subdivisions.

Loudoun Water, formerly known as the Loudoun County Sanitation Authority, owns and operates a centralized water and sewer system that serves the developed area of eastern Loudoun as shown in Figure 1. The Town of Leesburg provides treated Potomac River water to residents inside the Town limits, and to several residential areas adjacent to its eastern boundary. Outside of the Leesburg and Loudoun Water central service areas, county residents obtain water primarily from wells. In the rural towns and several of the subdivisions, water may come from communal water systems and sewage is treated in small wastewater treatment plants. The remaining single-family homes and businesses have on-site individual wastewater treatment systems.




Figure 1. Major features of Loudoun County, VA.

Physiography and Geology

Loudoun County intersects two physiographic provinces which are separated by the Bull Run Fault (Figure 1). The fault separates the Culpeper Basin (a Triassic-age rift basin) of the Piedmont Province on the east from the Blue Ridge Province to the west. The Culpeper Basin is comprised of sedimentary rocks and sedimentary-derived metamorphic rocks, both of which may include intrusions of dense, igneous diabase rock. The north-eastern area of the county, generally from the Town of Leesburg northward, is underlain by limestone conglomerate rock (the Leesburg Member of the Balls Bluff Siltstone) and has the surface features and hydrogeologic characteristics of a karst environment. Western Loudoun is underlain by metamorphic rocks derived from both sedimentary and igneous parent material. Bedrock in the county is covered by regolith (unconsolidated sediments and soils) that is commonly between 20 and 50 feet thick, but ranges from 0 to more than 90 feet thick. Soils are generally less permeable in eastern Loudoun compared to western Loudoun.

Watersheds

Watersheds are defined by topography and drain all of the surface water in an area to a single location such as a stream or lake. They are often used to delineate areas for monitoring, analyzing, and managing water resources. Watersheds can be defined at many different scales but the watershed scale that is most convenient for county-wide investigations in Loudoun is based on the 17 watershed areas shown in Figure 2. The majority of the county is covered by three major drainage areas that empty into the Potomac River by way of the following stream systems: Goose Creek, Catoctin Creek, and Broad Run.

The eastern and southern borders of the county share watersheds with the neighboring Virginia counties of Fairfax, Prince William, and Fauquier. The upper reaches of Broad Run and Sugarland Run watersheds lie to the east in Fairfax County and Goose Creek originates to the southwest in Fauquier County, but all three streams/watersheds drain into Loudoun County and ultimately the Potomac River.

The southeastern region of Loudoun includes the headwaters of Bull Run and Cub Run. These streams drain out of Loudoun County to the south and are tributaries to the Occoquan River which eventually discharges into the Potomac River.




Figure 2. Watersheds and streams in and adjacent to Loudoun County, VA.

WATER QUANTITY

This section presents information on the quantity of water resources with data on precipitation, streamflows, and groundwater levels in Loudoun County during calendar year 2013.

Precipitation

Total annual precipitation in 2014, 46.1 inches, was 4.7 inches above the normal (mean) annual precipitation of 41.3 inches for the full period of annual records of 1964 to 2014 at the Dulles Airport monitoring station. Precipitation data used in the WRMP are obtained from seven monitoring sites in the county (Figure 3). Four precipitation stations are part of the National Weather Service's (NWS) cooperative monitoring network and two rain gages are operated by the U.S. Geological Survey (USGS). The NWS sites have relatively long periods of record with one having nearly continuous data since 1930 (Table 1). The two USGS rain gages have mostly continuous data records beginning in 2004 and 2005 and provide data at 5-minute intervals.

Data from the long-term records indicate that annual precipitation has ranged from 20.4 inches (at the Lincoln station in 1930) to 67.7 inches (at the Sterling station in 2003). For purposes of identifying "normal" (mean) conditions and for comparison to current conditions, the standard practice is to group climatic data into periods of 30 consecutive years with the most recent year of the group ending in "0". For the 30-year period of 1981 through 2010, the normal annual precipitation at the Dulles station was 41.3 inches.




Figure 3. Precipitation monitoring sites.

Table 1. Precipitation monitoring stations and data.

Precipitation Monitoring Station Name	Start of Record ¹	Station Operated by ^{2, 3}	Annual Statistics (Inches) for Period of Record ⁴			2014 Total (Inches) ³	Days missing in 2014
			Minimum	Median	Maximum		
Blue Ridge Center ⁵	2011	Loudoun	31.7	40.7	50.5	43.7	0
Dulles	1964	NWS-COOP	27.0	39.5	65.7	46.1	0
Limestone Branch	2004	USGS	28.0	38.6	76.1	42.7	0
Lincoln	1930	NWS-COOP	20.4	41.3	63.5	41.4	48
Lovettsville	2005	USGS	27.6	38.0	61.3	38.7	0
Mt. Weather	1949	NWS-COOP	24.8	40.1	64.1	48.6	0
Sterling RCS	1978	NWS	30.3	42.7	67.7	43.1	0

¹ First full year that generally continuous data collection began.

² National Weather Service Cooperative weather station; U.S. Geological Survey; Loudoun County Government

³ NWS-COOP stations record liquid & frozen precipitation; USGS & Loudoun stations record rainfall only.

⁴ Annual precipitation statistics based on site's period of available record through 2014 (see footnote 1).

⁵ Only four complete years of data (2011-2014) exists for this monitoring station.

Figure 4 presents annual precipitation data from the Dulles station from 1981 through 2014. Annual precipitation has alternated above and below the 30-year median for the last several years so that there has not been a prolonged, multi-year deficit or surplus of precipitation.

In 2014 there were over 700,000 precipitation records collected at the seven stations.




Figure 4. Annual precipitation at Dulles Airport from 1981 through 2014.

Figure 5 shows 2014 monthly precipitation at the Dulles station in relation to monthly data for the 30-year period from 1981 through 2010. The data indicate that during 2014, February, April, May and August were above normal in rainfall, while July and September were below normal.

The National Climatic Data Center reports on storms and tornadoes such as the touchdown in Middleburg on May 16, 2014.




Figure 5. Monthly precipitation at Dulles Airport.

A graph of daily precipitation at the Dulles station is shown in Figure 6. Only one day during 2014 received a rainfall total greater than two inches. The largest storm occurred around April 30 with 3.99 inches and a weekly total of 5.48 inches. Over the entire year, there were 242 days with no recorded precipitation at the Dulles station.




Figure 6. Daily precipitation at Dulles Airport in 2014.

Snowfall

Of the total precipitation at the Dulles station during 2014-2015 season, frozen precipitation totaled 34.3 inches, which was above the normal annual total of 18.9 inches of frozen precipitation and well below the 74.7 inches in winter season 2009-2010. Note that frozen precipitation contributes to the total (liquid) reported precipitation, however, at a reduced ratio based on the characteristics of the frozen precipitation. For example, heavy snow may be a 3 to 1 ratio (3 in of snow = 1 in of water) while dry, powdery snow may be 50 to 1 or more. Snowfall totals are reported by season during the winter and early spring months. The total snow depths are aggregated from daily values recorded at three weather stations operated by the National Weather Services as shown in Figure 7. The average total of the three stations for each season is also shown.




Figure 7. Seasonal snowfall totals.

Streamflow

Perennial streams flow all or most of the year. In the past, the USGS has estimated that Loudoun County has approximately 507 miles of perennial streams while more recent investigations using additional data and standardized methodologies have indicated that the county may have over 1,500 miles of perennial streams. Knowing how much water flows in the larger perennial streams and how it varies over both short and long time periods is useful in the assessment of floodplains, flood control, stormwater structures, and environmental conditions. There are 10 stream gages that measure and record water stage (level) in Loudoun County streams (Figure 8). Measured water levels at each gaging station are reported via telemetry to the USGS, correlated to historical site-specific stream discharges (flows), and the data posted in near real-time with updates normally every 15 minutes. The data are available at [the USGS web site for Loudoun County](#). Three additional stream gages are located along the county's perimeter: at [Harpers Ferry](#) and [Point of Rocks](#) on the Potomac River (both with real-time data on an internet web page) and on Bull Run near Route 705.



Figure 8. Locations of stream gaging stations.

2014 Water Resources Monitoring Data Summary

The USGS regularly inspects the gaging stations to check the monitoring equipment and measure stream channel cross sections, water levels, and streamflow velocities in order to maintain calibration and data accuracy. However, data are considered provisional until passing the USGS's full quality control process.




Figure 9. Stream discharge hydrograph for Goose Creek during 2014 compared to data from 1981-2010.

Figure 9 illustrates mean daily flow rates in Goose Creek near Leesburg during 2014 and compares it to monthly flow statistics at the same site for the period 1981 through 2010. These data indicate that streamflows were above normal from January through July, then dropping to below normal in August to October and above normal in December. Spikes in streamflow are generally correlated with rainfall at Dulles Airport (Figure 6). These two monitoring sites are approximately 5 miles apart, but the upper reaches of the watershed are over 30 miles from the Dulles precipitation station. If a storm event is localized in the upper area of the watershed, it can result in a relatively high stream discharge even though reported precipitation at the Dulles site is relatively low. The highest peak stream discharge recorded in 2014 at this station occurred on May 16. Goose Creek is the County's largest stream, with its headwaters in Fauquier County, flowing across Loudoun County, and discharging to the Potomac River.

Table 2 lists the 10 gaging stations in the county along with selected data statistics. The peak flow rates for 2014 occurred on May 16 at all of the stream gages.

Table 2. Stream gaging stations and basic statistics.

Stream Gage Site Name	Start of Record	Drainage Area ¹ (sq. miles)	2014 Avg ² (cfs)	Previous Historic Avg ³ (cfs)	2014 Min ⁴ (cfs)	Previous Historic Min ⁵ (cfs)	2014 Peak ⁶ (cfs)	Previous Historic Peak ⁷ (cfs)	2014 Non-flowing ⁸ (days)	Average Annual Historic Non-flowing ⁹ (days)
Beaverdam Creek	Jul 2001	47.2	57.9	50.5	0.0	0.0	1,580	5,000	11	22.5
Broad Run	Oct 2001	76.1	141.6	131.5	9.7	1.3	3,810	10,300	0	0
Catoctin Creek - Taylorstown	Oct 1970	89.5	173.3	102.5	8.4	0.1	5,000	6,770	0	1.9
Goose Creek - Leesburg	Jul 1909	332.0	416.9	355.4	27.0	1.1	7,260	20,800	0	0
Goose Creek - Middleburg	Oct 1965	122.0	161.4	136.7	0.0	0.0	2,580	14,000	0	5.4
Limestone Branch	Aug 2001	7.9	13.3	8.7	0.9	0.4	521	976	0	0
North Fork Catoctin Creek	Jul 2001	23.1	32.9	24.3	8.4	0.0	929	1,190	1	9.6
North Fork Goose Creek	Jul 2001	38.1	50.0	48.3	3.5	0.2	1,300	3,040	2	0
Piney Run	Oct 2001	13.5	20.4	14.0	1.7	0.0	367	488	0	2.6
South Fork Catoctin Creek	Jul 2001	31.6	48.4	36.3	3.5	0.0	1,530	1,920	4	3.7

¹ Drainage area above the stream gage (square miles)

² Average daily flow rate during 2014

³ Average daily flow rate for the period 2002–2013

⁴ Lowest 7-day average flow rate during 2014. Note: Broad Run flow augmented by wastewater discharge up to 11 MGD starting in 2008.

⁵ The lowest 7-day average flow rate for the period 2002–2013

⁶ Peak daily flow rate during 2014

⁷ Peak daily flow rate for the period 2002–2013

⁸ Maximum number of consecutive days with very low flow (below 0.2 cfs) during 2014

⁹ Maximum number of consecutive days per year with less than 0.2 cfs flow during the period 2002–2013

Groundwater Levels and Wells

There are more than 14,500 active water supply wells throughout Loudoun County. Groundwater is the primary source of drinking water for the majority of residents in western Loudoun. Groundwater levels during 2014 were recorded at 20 dedicated monitoring wells at the sites shown in Figure 10 and included in the County's Water Resources Monitoring Program. Seventeen of these wells are operated by staff from the Department of Building and Development and three are operated by the USGS. Groundwater level data have been collected from the three USGS wells since the late 1960s or early 1970s. Most of the County-monitored wells were established as monitoring sites within the past decade, with one well dating back to 2002. Table 3 lists the monitoring wells, basic information about each well, and groundwater level data for both 2014 and the well's historic record.




Figure 10. Locations of groundwater monitoring wells.

Table 3. Monitoring wells and groundwater level data for 2014.

Well Site ID (see map for location)	Monitoring Organization	Well Depth (feet)	Rock Type	Period of Record	Groundwater Level (feet) ^{1, 2}			
					Historic High	2014 High	Historic Low	2014 Low
USGS-01	USGS	516	Meta-conglomerate/metasiltstone	8/1969 - Present	1013.9	1010.5	1000.3	1001.6
USGS-02	USGS	535	Fluvial, deltaic sandstone	10/1977 - Present	363.2	363.1	334.4	349.9
USGS-03	USGS	165	Siltstone/sandstone	11/1968 - Present	416.3	415.6	410.6	411.35
BOLN-12	Loudoun	515	Fluvial, deltaic sandstone	12/2006 - Present	347.0	347.0	339.7	342.1
BRCS-01	Loudoun	320	Igneous intrusive	12/2007 - Present	532.8	528.8	521.1	522.4
HARM-01	Loudoun	945	Plutonic igneous intrusive	2/2005 - Present	505.4	505.4	467.4	494.5
MGRD-01	Loudoun	400	Plutonic igneous intrusive	12/2007 - Present	491.9	491.9	477.4	485.4
RGER-01	Loudoun	700	Igneous intrusive	2/2005 - Present	664.9	663.1	652.2	652.3
TSPG-01	Loudoun	360	Plutonic igneous intrusive	2/2005 - Present	435.3	432.8	419.1	425.6
WDGR-01	Loudoun	940	Mafic igneous intrusive	3/2005 - Present	646.8	644.1	629.6	632.8
WFRD-01	Loudoun	400	Plutonic igneous intrusive	11/2002 - Present	421.8	416.6	399.7	403.5
BRPK-01	Loudoun	680	Igneous intrusive	7/2009 - Present	1647.8	1645.6	1632.5	1633.7
THPK-01	Loudoun	360	Limestone conglomerate	7/2009 - Present	195.3	187.5	173.6	175.4
ALPK-01	Loudoun	240	Alluvium/metasiltstone	7/2009 - Present	214.4	211.7	193.6	197.8
HRKN-01	Loudoun	600	Plutonic igneous intrusive	3/2009 - Present	688.5	669.4	643.3	655.8
VRGO-01 ³	Loudoun	300	Igneous intrusive	3/2009 - Present	563.1	561.8	538.4	542.5
EVGN-01	Loudoun	320	Diabase	3/2009 - Present	309.2	309.2	300.7	300.4
LNSF-01	Loudoun	322	Hornfels	8/2013 - Present	287.7	287.7	276.4	276.4
LWTP-01 ³	Loudoun	250	Metasiltstone	3/2009 - Present	288.8	288.8	273.3	273.3

¹ Elevation above mean sea level.

² Historic data highs and lows are during the period of record through 2014.

³ Partial year data.

Boxes indicate new historic Highs/Lows set during 2014.

Figure 11 shows hydrographs for selected monitoring wells that are representative of groundwater levels in the county for calendar year 2014. Short-term natural increases in groundwater levels occur because of recharge from precipitation. In the absence of additional recharge from precipitation and outside influences such as nearby pumping, groundwater levels normally exhibit a steady, slow decline over time after rain events. Groundwater levels are typically highest in late spring/early summer and lowest in late fall/early winter. Assuming normal precipitation patterns, this is due to greater recharge to the groundwater system during cooler winter/spring weather when evapotranspiration is low, thereby allowing more water to infiltrate downward to the water table.




Figure 12. Groundwater hydrograph and daily rainfall in 2014.




Figure 13. Number of wells constructed in Loudoun County between 1980 and 2014.




Figure 11. Groundwater levels from selected County WRMP monitoring wells.

Figure 12 shows a hydrograph from monitoring well BRCS-01 and daily rainfall from the BRCS rain gage. The well and rain gage are located approximately 50 feet apart from each other. Both data sets are during 2014 and show the response of groundwater levels to precipitation events. Note that during late summer, when conditions are generally dryer and evapotranspiration is highest, response to even significant rain events will produce only subtle increases in groundwater level.

During 2014, 194 new water supply wells were constructed. Figure 13 presents the number of wells drilled each year since 1980. The installation of new wells is primarily driven by the pace of residential construction and, occasionally, zoning changes affecting residential development potential. As occurred during the previous three to four years, the number of new wells drilled in 2013 remained relatively low. The median total depth of wells installed in 2014 was 460 feet with the depths ranging from 140 to 1,160 feet. The median estimated yield (based on air-lift pumping) was 7.0 gallons per minute with yields ranging from 0 to 140 gallons per minute.

The median depth of wells drilled in Loudoun County has increased from 150 feet in the 1960's to the current median of 410 feet. The increase has been possible because of advances in drilling technology, allowing wells to be drilled cheaper, quicker and deeper to provide increased water storage.

WATER QUALITY

The quality of surface water in Loudoun County was quantified in 2014 using several metrics including chemical, microbiological, and benthic macroinvertebrates. Groundwater quality was assessed through chemical and bacteria analyses conducted on well water samples. Monitoring results from each of these data types are discussed below.

Surface Water Chemistry

Chemical sampling and analysis of surface water in 2014 was primarily conducted by the Virginia Department of Environmental Quality (DEQ) as part of their state-wide surface water quality sampling program.

In 2014, DEQ collected samples from 17 sites and conducted 311 analyses of nitrogen and phosphorous from the watersheds of Loudoun County (some watershed boundaries extend beyond the County's boundaries). Nutrient enrichment has been identified as a major cause of the reported stream impairments nationwide and can lead to low dissolved oxygen, fish kills, shifts in flora and fauna and blooms of nuisance algae. Figure 14 illustrates the results of sampling by DEQ for nitrogen and phosphorus in the surface waters from the watersheds of Loudoun County during 2014.

In 2000, the U.S. Environmental Protection Agency (EPA) developed ambient water quality criteria recommendations and information for 14 nutrient eco-regions in the continental United States. Individual states could adopt the criteria developed by EPA or elect to develop their own criteria and methodologies. Virginia has been working on a methodology to evaluate nutrient stress in wadeable streams since that time. As shown in Figure 14, the percent of stream samples which exceed the threshold levels for nitrogen and phosphorous between 2000 and 2014 are shown. In 2014, approximately 75 percent and 43 percent of the samples collected by DEQ contained nitrogen and phosphorus concentrations above the 0.69 mg/L and 0.037 mg/L EPA guidance criteria, respectively.

Surface Water Microbiology

The primary microbiological area of concern for surface water relates to pathogens that may adversely affect human health. An accepted practice to test for pathogens from human and warm-blooded animal waste is to test water for *Escherichia coli* (*E. coli*) bacteria as an indicator of waste contamination. EPA uses *E. coli* concentrations as an indicator of whether the water is considered safe for humans after casual contact. This criterion is identified by EPA as "recreational use" and includes activities such as swimming, fishing and boating.

In 2014, DEQ collected and analyzed 62 samples from the watersheds of Loudoun County and found that approximately 80 percent were above the recreational limit of 235 *E. coli* colonies per 100 milliliters. Stream segments that are tested and exceed the recreational use criteria more than 10.5 percent of the time may be identified as "impaired" by DEQ. Using a similar approach, Table 4 summarizes the number of sites in which more than 10.5 percent of the samples exceeded the recreational limit over the last 5 years. Several programs are in place to reduce bacterial contamination in the impaired surface waters of Loudoun County including initiatives to repair or upgrade on-site wastewater treatment systems (e.g., septic systems and drain fields), reduce pet waste, and fence livestock out of streams.




Figure 14. Nutrient concentrations as percent of samples exceeding EPA guidance thresholds from 2000 to 2014.

Table 4. Summary of surface water microbiological testing by DEQ.

Year	Number of Samples	Number of Monitoring Sites	Number of Sites Exceeding ¹	Percent Sites Exceeding ²
2009	101	16	13	81%
2010	122	20	8	90%
2011	124	24	19	85%
2012	117	24	19	79%
2013	136	20	19	95%
2014	62	10	8	80%


¹ Exceeds recreational use criteria for *Escherichia coli* in more than 10.5% of the samples .

² Percent of the sites when more than 10.5% of samples exceeded recreational use criteria.

Benthic Macroinvertebrates

Benthic macroinvertebrates are stream bottom-dwelling invertebrate organisms (mostly insect larvae) that can be seen without magnification. Their tolerance of poor water quality varies depending on the species and, as a result, these organisms are used as indicators of water quality.

Sampling a stream for benthic macro-invertebrates usually involves collecting all the organisms within a small area of the stream bottom, identifying the types of organisms collected to the order, family or genus taxa level, and counting the number of each type. These results are then converted to a “macroinvertebrate score” which is used to qualitatively grade the water quality. In 2014, two techniques were used to evaluate the benthic macro-invertebrate populations: the Virginia Stream Condition Index (VA SCI) at both the family and genus level used by DEQ and the Virginia Save Our Streams (VA SOS) index used by several citizen volunteer organizations in and adjacent to the county.



During the period 2009 through 2014, DEQ sampled a total of 87 times at 45 locations in Loudoun and calculated VA SCI scores which ranged from Severe Stress to Excellent. Figure 15 illustrates the average stream conditions from benthic samples collected by DEQ between 2009 and 2014.

Figure 15. Summary of DEQ benthic monitoring results.

Several volunteer organizations in Loudoun Watershed Watch collect benthic macro-invertebrate data. From 2009 through 2014, Loudoun Wildlife Conservancy, Goose Creek Association, and other volunteer groups collected 147 samples from approximately 56 locations using the VA SOS methodology. Results ranged from Acceptable to Unacceptable as shown in Figure 16.

Benthic macroinvertebrate species vary in their tolerance of poor water quality. Monitoring benthic populations is an efficient way for professionals and volunteers to assess one aspect of stream water quality.




Figure 16. Summary of volunteer benthic monitoring results.

Stream Impairments

Each year, DEQ tests a statistically significant fraction of Virginia's streams, rivers, lakes, and tidal waters as part of their water quality assessment program. Over 130 different pollutants are monitored to determine whether the waters can be safely used for swimming, fishing and drinking. Waters that do not meet the adopted standards are reported to EPA in the Clean Water Act 303(d) Impaired Waters Report. DEQ has developed lists of impaired waters every even calendar year since 1992. In Loudoun County, DEQ water quality impairments have included:

- aquatic life (benthic macroinvertebrates)
- recreational/swimming (bacteria)
- fishing/consumption (tissue analysis)

In the latest report released in December 15, 2014, there were over 175 stream miles in Loudoun County identified as impaired for one or more criteria. Listing a stream as “impaired” begins a multi-year process of identifying pollution sources, determining appropriate pollution loadings, and designing and implementing corrective measures. Figure 17 through Figure 20 illustrate the impairments for aquatic life use, recreational/swimming use, fish consumption and public water supply, respectively. It is anticipated that in 2016 EPA will approve the 2014 305(b)/303(d) Water Quality Assessment Integrated Draft Report.

Surface water quality impairments are reported to the Environmental Protection Agency every two years by the Virginia Department of Environmental Quality (DEQ). The Draft 2014 305(b)/303(d) Water Quality Assessment Integrated Report (Integrated Report) summarizes the water quality conditions from Jan. 1, 2007, to Dec. 31, 2012.




Figure 17. Aquatic life use (benthic macroinvertebrates) impaired stream segments.




Figure 18. Recreational/swimming use (bacteria) impaired stream segments.




Figure 19. Fish consumption use (PCB and mercury in fish tissue) impaired stream segments.




Figure 20. Public water supply use (chemicals) impaired stream segments.

Groundwater Quality

Groundwater is the source of drinking water for most of Loudoun County outside of Loudoun Water's central service area (see Figure 1) and the Town of Leesburg. Information on groundwater quality is obtained from several sources. Before new potable water wells can be used, they must be tested and pass drinking water quality standards for a wide range of chemical parameters listed by the County Health Department. In 2014, groundwater samples collected and analyzed from new wells were generally consistent with historical data (Table 5). There are large areas of the county that have elevated levels of iron and manganese; aesthetic contaminants that do not adversely affect human health at the concentrations found in the county. In general, groundwater quality in the county is good.

Table 5. Statistics for selected groundwater chemistry parameters.

Analyte	MCL(mg/L)	Samples	# above MCL	% above MCL
Nitrate	10	All 3722	19	0.5
		2014 178	4	2.2
Sulfate	250	All 3722	15	0.4
		2014 178	1	0.6
Lead	0.015	All 3725	39	1.0
		2014 178	2	1.9
Fluoride	4	All 3722	8	0.2
		2014 178	1	0.6
Arsenic	0.01	All 3729	18	0.5
		2014 178	2	1.1
Manganese	0.05*	All 3729	2439	65.4
		2014 178	129	72.5
Iron	0.3*	All 3745	2578	68.8
		2014 178	149	83.7
TDS	500*	All 3724	28	0.8
		2014 178	2	1.1

* Secondary MCL for taste, color, and odor.

The most prevalent sources of potential groundwater pollution are the on-site wastewater treatment systems (OWTS) serving homes and small businesses in the rural areas of the county. There are approximately 15,000 active OWTSs in the county and during 2014, 188 new OWTSs were installed. An OWTS that is properly installed and serviced should not pose a threat to groundwater quality. However, improper OWTS installation or maintenance can cause wastewater to be untreated or undertreated and lead to groundwater or surface water contamination. Because OWTSs are typically used in areas with private water wells, it is important to properly maintain the OWTS and regularly have the well water sampled and tested to assure that it is safe to drink. The Loudoun County Department of Environmental Health can provide information on maintenance and testing of private water wells and OWTSs (703-777-0234 and www.loudoun.gov/onsite).

There are a few isolated locations in the County where significant groundwater contamination is known to exist. The most notable location is the Hidden Lane Landfill in northeast Loudoun, which was placed on the EPA's National Priorities List (Superfund). The EPA has developed fact sheets to update citizens on clean-up and investigation activities at the site. The latest Hidden Lane fact sheet and more information can be found by visiting the [EPA web site](#).

Of the 178 groundwater samples reported in 2014, ten samples had individual analyte concentrations higher than the EPA Maximum Contaminant Level (MCL); one for sulfate, two for lead, four for nitrate, two for arsenic, and one for fluoride. Groundwater quality in Loudoun is generally good, but these data show why private drinking water well owners should have their well water tested regularly to assure that the water is safe to consume.

WATER RESOURCES 2014 HIGHLIGHT:

VIRGINIA STORMWATER MANAGEMENT PROGRAM (VSMP)

On July 1, 2014, Loudoun County was established as a Virginia Stormwater Management Program (VSMP) Authority, as required by the Virginia Stormwater Management Act. The new regulations are adopted in Chapter 1096 of the Loudoun County Codified Ordinances and Chapter 5 of the Facilities Standards Manual (FSM).

As a VSMP Authority, the County issues and administers permits for regulated land disturbing activities to ensure compliance with the regulations both during and after construction. The process includes plan review and approval, site inspections during and after construction, and operation and maintenance of the SWM system following construction. In addition, the County's program is overseen by the Virginia Department of Environmental Quality (DEQ), which also issues permit coverage under the state's VPDES Construction General Permit. This "dual coverage" by the County and the state must be obtained prior to land disturbance.

PROGRAM OVERVIEW

Stormwater Management (SWM) entails control of both the quantity and quality of stormwater runoff. Its proper implementation is an essential part of land development, both during and after construction, because the associated increases to the runoff volume and peak flow rate and the disruption of natural drainage patterns can lead to damage of downstream properties in the form of erosion, sediment deposition, and/or flooding. Similarly, increases in pollutant discharge and water temperature can lead to degradation of the quality of water flowing through natural streams, which can negatively affect public health, as well as recreational and economic pursuits and aquatic habitat. Accordingly, a chief goal of SWM strategies, design, and Best Management Practices (BMPs) is to replicate pre-development drainage patterns and pollutant loading from non-point sources.



SWM has been implemented in Loudoun County in various forms since the late 1980s, through tools such as development proffers, regional water quality standards, and various technical standards located in the Loudoun County Facilities Standards Manual. Such efforts culminated in Loudoun's first Stormwater Management Program, which was established by ordinance in 2003.

For more information about the VSMP, contact Department of Building & Development, by email or by calling 703-777-0220.

More information about Loudoun County's water resources monitoring program can be obtained at:

www.loudoun.gov/watermonitoring

2014 – Moment to Remember




Photo credit – Helen Van Ryzin



Photo credit – Kevin Bills, Corcoran Brewing

On May 16, 2014 over 3 inches of rain caused localized flooding on South Fork Catotcin Creek near the Village of Waterford and within the Town of Purcellville.